АБРАЗИВОУСТОЙЧИВИ - ABRASION RESISTANT

720AA S&D 10 bar Alfagomma





Смукателно-нагнетателен маркуч за насипни материали.
Вътрешна камера: черна електропроводима EPDM.
Вградени текстилни оплетки с висока якост и вградена стоманена спирала.
Външна обвивка: - черна електропроводима SBR/NR, устойчива на абразии и озон.
Температурен режим: -30°C +80°C.
Приложение: за пренос на насипни материали при тежък режим на работа. Специално за сух цимент, пясък, земна маса, чакъл, семена, фуражи и др.

Suction and delivery hose for bulk materials.
Tube: black conductive NR - abrasion resistant.
Reinforcement: : high tensile textile cords with embedded steel helix wire.
Cover: black conductive SBR/NR - abrasion and ozone resistant.
Working temperature: -30°C +80°C.
Application: bulk material suction and delivery in heavy duty applications. Specially designed for dry cement, sand, gravel, grain and animal feed transfer, etc.

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		радиус на огъване / BR	вак. % vac. %	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	mm	bar	kg/m
720050	51	2"	65	2,56	10	150	30	450	153	100,0	1,430
720063	63	2,1/2"	77	3,03	10	150	30	450	189	90,0	1,900
720076	76	3"	90	3,54	10	150	30	450	228	90,0	2,280
720090	90	3,1/2"	106	4,17	10	150	30	450	270	90,0	3,230
720100	102	4"	118	4,65	10	150	30	450	306	90,0	3,600
720127	127	5"	145	5,71	5	75	15	225	508	80,0	5,270
720152	152	6"	168	6,61	5	75	15	225	608	80,0	5,950
720203	203	8"	221	8,70	5	75	15	225	812	70,0	8,990