ХИМИКАЛИ - CHEMICALS

UHMWPE 529AA S&D 16 bar Alfagomma



Смукателно-нагнетателен маркуч за химикали.
Вътрешна камера: черна електропроводима, от UHMWPE (Ултра високо молекулен полиетилен).
Вградени текстилни оплетки с висока якост и вградена стоманена спирала - антистатична.
Външна обвивка: - черна електропроводима EPDM, пожароустойчива, устойчива на абразии и озон.
Температурен режим: -30°C +100°C.
Приложение: за пренос на киселини и химикали. Подходящ за 98% от съществуващите химикали.
Подходящ за употреба в среди с потенциална опасност от експлозии.

Suction and delivery hose for chemicals.
Tube: black conductive UHMWPE (Ultra High Molecular Weight Polyethylene).
Reinforcement: : high tensile textile cords with embedded steel helix wire - antistatic wire.
Cover: black conductive EPDM - abrasion, ozone and fire resistant.
Working temperature: -30°C +100°C.
Application: acid and chemical suction and delivery. Suitable for 98% of existing chemicals.
Suitable to be used in potentially explosive environment.

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		радиус на огъване / BR	вак. % vac. %	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	mm	bar	kg/m
529AA020	19	3/4"	31	1,22	16	240	64	960	114	90,0	0,670
529AA025	25	1"	37	1,46	16	240	64	960	150	90,0	0,830
529AA032	32	1,1/4"	44	1,73	16	240	64	960	192	90,0	1,000
529AA038	38	1,1/2"	51	2,01	16	240	64	960	228	90,0	1,300
529AA050	51	2"	66	2,60	16	240	64	960	300	90,0	1,960
529AA063	63	2,1/2"	77	3,03	16	240	64	960	378	90,0	2,480
529AA075	76	3"	92	3,62	16	240	64	960	450	80,0	3,110
529AA100	102	4"	118	4,65	16	240	64	960	600	80,0	4,190