МЕТАН - CNG

CNG5000 15R 350bar



Маркуч високо налягане за пренос на CNG, електропроводима вложка против статично напрежение.
Вътрешна камера: коекструдиран електропроводим полиамид и полиамид PA12.
Една или две арамидни оплетки и една оплетка от синтетично влакно.
Външна обвивка: червен полиуретан, с микроперфорация, устойчив на абразия.
Температурен режим: -40°C +85°C.
Приложение: Маркуч за пренос и зареждане на CNG гориво за мобилни и стационарни станции, резервоари, цистерни. Много лек и гъвкав, здрава външна обвивка, устойчива на бразии.

High pressure hose for CNG refueling applications, conductive inner tube to dissipate static charge.
Tube: coextruded conductive polyamide and polyamide PA12.
Reinforcement: one or two braids of aramid fiber plus one braid of synthetic fiber.
Cover: red polyurethane, pinpricked, abrasion resistant.
Working temperature: -40°C +85°C.
Application: Refueling hose for mobile and stationary units used to refill natural gas vehicles tanks, CNG transfer lines. Non metalic design, lightweight and flexibility, extra tough cover for abrasion.

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		радиус на огъване / BR	вак. % vac. %	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	mm	bar	kg/m
CNG500006	6,5	1/4"	13,7	35/64"	350	5250	1400	21000	50		0,126
CNG500010	9,7	3/8"	18,9	3/4"	350	5250	1400	21000	70		0,219
CNG500012	13,0	1/2"	22,5	57/64"	350	5250	1400	21000	90		0,285
CNG500020	19,5	3/4"	29,6	1,11/64"	350	5250	1400	21000	180		0,406
CNG500025	25,6	1"	39,0	1,17/32"	350	5250	1400	21000	200		0,724