АБРАЗИВОУСТОЙЧИВИ - ABRASION RESISTANT

SM40 Semperit 40 bar за мазилки / Plaster





Нагнетателен маркуч за абразивни материали - фугиращи смеси, замазки, мазилки, гипс и др.

Вътрешна камера: черна SBR/NR/BR, устойчива на абразия, антистатична, гладка.

Текстилни оплетки с висока якост.

Външна обвивка: черна SBR, устойчива на озон и атмосферни влияния.

Температурен режим: -35°C +80°C.

Приложение: Много дълъг експлоатационен живот благодарение на устойчивото на абразия качество на вътрешната камера и обвивката. Средно износване на вътрешната камера 70 mm3 (according to DIN ISO 4649:2021). Компактният подсилващ пакет осигурява много стабилно напречено сечение, което прави маркуча силно устойчив на огъване, както и придава добра устойчивост на високо налягане. Антистатичната конструкция предотвратява натрупването на статично електричество.

Delivery hose for abrasive materials - grout, screed, plaster and gypsum in compact flow process.

Tube: black SBR/NR/BR, abrasion resistant, antistatic, smooth.

Reinforcement: Textile wrapped.

Cover: black SBR, resistant to ozone and weather, cloth impression.

Working temperature: -35°C +80°C.

Application: Very long service life due to abrasion resistant quality of the rubber tube nad cover. Average wear of the tube 70 mm^3 (according to DIN ISO 4649:2021). The compact reinforcement package provides a very stable cross-section making the hose highly kink resistant and also offers high pressure resistance. Antistatic construction prevents the build-up of static electricity.

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		радиус на огъване / BR	вак.% vac%	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	mm	bar	kg/m
SM40025	25	1"	39	1,17/32"	40	600	100	1500	250		0,800
SM40035	35	1,3/8"	49	1,59/64"	40	600	100	1500	350		1,150
SM40050	50	2"	68	2,43/64"	40	600	100	1500	500		1,950
SM40065	65	2,1/2"	83	3,17/64	40	600	100	1500	650		2,550