МАСЛА И ГОРИВА - MINERAL OILS, FUELS

619AA - Alfagomma 16bar / EN 12115



Смукателно-нагнетателен маркуч за горива и масла.
Вътрешна камера: черна, електропроводима CR, устойчива на абразия, озон, въглеводороди и огън.
Синтетични оплетки с висока якост с вградена метална спирала - антистатична.
Външна обвивка: черна електропроводима CR, устойчива на абразия, озон, въглеводороди и огън.
Температурен режим: -30°C +70°C.
Приложение: предназначен за дълъг живот при тежък работен режим. Подходящ за употреба в потенциално взривоопасни среди.

Suction and delivery hose for fuel and oil.
Tube: black, conductive CR, abrasion, ozone, hydrocarbon and fire resistant.
Reinforcement: high tensile textile cords with embedded steel helix wire - antistatic wire.
Cover: black conductive CR - abrasion, ozone, hydrocarbon and fire resistant.
Working temperature: -30°C +70°C.
Application: designed for long service life in heavy duty applications. Suitable to be used in potentially explosive environments.

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		радиус на огъване / BR	вак. % vac. %	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	mm		kg/m
619AA050	51,0	2"	67,0		16	240	64	960	275	100,0	2,010
619AA075	76,0	3"	92,0		16	240	64	450	350	90,0	2,820
619AA100	102,0	4"	118,0		16	240	64	450	450	90,0	3,820