ГАЗ ПРОПАН-БУТАН - LPG

659AA 25bar Delivery - Alfagomma EN1762



Нагнетателен маркуч за LPG, отговарящ на изискванията на EN1762
Вътрешна камера: черна NBR.
Текстилно оплетки с висока якост, антистатичен проводник.
Външна обвивка: черна CR, устойчива на абразия, озон, въглеводород, пожароустойчива, с микро-перфорация.
Температурен режим: -30°C +70°C.
Приложение: Нагнетателен маркуч за LPG, съответства на изискванията на EN1762. Подходящ за газ-станции, резервоари,цистерни и др. Спциално за тежък режим на работа при навиване на макари.

Delivery hose for LPG, coreesponding to the requirements of EN1762.
Tube: black NBR.
Reinforcement: high tensile textile braids - antistatic wire.
Cover: black CR, abrasion, ozone, hydrocarbon and fire resistant, pin pricked.
Working temperature: -30°C +70°C.
Application: Delivery hose for LPG, in accordance with EN1762. Suitable for gas stations, cisterns,tanks, truck tanks, etc. Specially designed for heavy duty reeling applications.

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		радиус на огъване / BR	вак. % vac. %	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	mm	bar	kg/m
LPG012	12	1/2"	23	29/32"	25	375	100	1500	100		0,390
LPG016	16	5/8"	26	1,1/32"	25	375	100	1500	125		0,450
LPG020	19	3/4"	31	1,7/32"	25	375	100	1500	160		0,550
LPG025	25	1"	38	1,1/2"	25	375	100	1500	200		0,790
LPG032	32	1,1/4"	45	1,49/64"	25	375	100	1500	250		0,950
LPG038	38	1,1/2"	52	2,3/64"	25	375	100	1500	320		1,220
LPG050	51	2"	67	2,41/64"	25	375	100	1500	400		1,770