# МАСЛА И ГОРИВА - MINERAL OILS, FUELS

## FUB Semperit 12bar






**Висококачествен нагнетателен маркуч за безоловни горива (EN 228:2017) и дизелови масла (EN 590:2017).**
**Вътрешна камера: черна, гладка NBR, устойчива на масла, електропроводима.**
**Текстилна спирала.**
**Външна обвивка: черна NBR, устойчива на масла, озон и климатични условия, електропроводима.**
**Температурен режим: -40°C +100°C.**
**Приложение: може да се използва за E5 (EN 228:2017), E10, E85 и E100, както и за B7 (EN 590:2017), B20 и B100 (чист биодизел / 100% FAME/RME) с максимално съдържание на аромати 60%.**

**High quality delivery hose for unleaded fuels (EN 228:2017) and diesel oils (EN 590:2017)**
**Tube: black NBR, resistant to oil, electrically conductive, smooth.**
**Reinforcement: textile spiral.**
**Cover: Quality performance rubber, black, resistant to oil, ozone and weather, electrically conductive, smooth.**
**Working temperature: -40°C +100°C.**
**Application: it can be used for E5 (EN 228:2017), E10, E85 and E100 as well for B7 (EN 590:2017), B20 and B100 (pure biodiesel / 100% FAME/RME) with a maximum aromatic contet of 60%.**

| Кат. № / Part. № | вътрешен диаметър / ID | | външен диаметър / OD | | работно налягане / WP | | разрушаващо налягане / BP | | радиус на огъване / BR | вак. % vac. % | тегло/m weight/m |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | mm | inch | mm | inch | bar | psi | bar | psi | mm | | kg/m |
| **FUB3.2** | 3,2 | 1/8" | 9,2 | | 12 | 180 | 48 | 720 | 20 | | 0,080 |
| **FUB04** | 4 | | 10,0 | | 12 | 180 | 48 | 720 | 25 | | 0,080 |
| **FUB05** | 5 | 3/16" | 11,0 | | 12 | 180 | 48 | 720 | 30 | | 0,110 |
| **FUB06** | 6 | 1/4" | 12,0 | | 12 | 180 | 48 | 720 | 35 | | 0,100 |
| **FUB07** | 7 | | 13,0 | | 12 | 180 | 48 | 720 | 42 | | 0,120 |
| **FUB08** | 8 | 5/16" | 14,0 | | 12 | 180 | 48 | 720 | 50 | | 0,130 |
| **FUB10** | 10 | | 16,0 | | 12 | 180 | 48 | 720 | 60 | | 0,140 |
| **FUB12** | 12 | | 19,0 | | 12 | 180 | 48 | 720 | 70 | | 0,210 |