МАСЛА И ГОРИВА - MINERAL OILS, FUELS

Semperit - TM30 SD / 10bar



Смукателно-нагнетателен маркуч за пълнене и изпразване на резервоари.
Вътрешна камера: черна, гладка NBR, електропроводима.
Синтетични оплетки с висока якост, поцинакована двойна метална спирала (DN>50 поцинкована метална спирала), 2 кръстосани медни жици.
Външна обвивка: черна, гладка NBR/PVC, устойчива на масла, горива, озон и климатични условия.
Температурен режим: -40°C +100°C.
Application: suction and delivery hose for filling and discharging tanks, tetrol tankers and ships with unleaded fuels (EN228:2017), fuel oils (DIN 51 603 parts 1-5) and mineral oil-based hydraulic oils.

Suction and delivery hose for filling and discharging tanks.
Tube: black, smooth NBR rubber compound, electrically conductive.
Reinforcement: textile wrapped, zinc plated double steel wire helix (DN>50 zinc plated steel wire helix), 2 crossed copper wires.
Cover: SBR/EPDM, black, resistant to ozone and weather, abrasion resistant, resistant to oil (acc. to SAE J517:2017)
Working temperature: -40°C +90°C, за масла +100°C.
Application: suction and delivery hose for filling and discharging tanks, tetrol tankers and ships with unleaded fuels (EN228:2017), fuel oils (DIN 51 603 parts 1-5) and mineral oil-based hydraulic oils.

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		радиус на огъване / BR	вак. % vac. %	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	mm		kg/m
TM30020	19,0	3/4"	29,0		10	150	30	450	45		0,600
TM30025	25,0	1"	35,0		10	150	30	450	55		0,700
TM30032	32,0	1,1/4"	42,0		10	150	30	450	65		0,900
TM30038	38,0	1,1/2"	48,0		10	150	30	450	80		1,100
TM30040	40,0	1,9/16"	50,0		10	150	30	450	90		1,150
TM30050	51,0	2"	62,0		10	150	30	450	130		1,300
TM30063	63,0	2,1/2"	75,0		10	150	30	450	180		2,000
TM30076	76,0	3"	88,0		10	150	30	450	350		2,550
TM30100	102,0	4"	116,0		10	150	30	450	400		3,900