ПОЛИУРЕТАНОВИ МАРКУЧИ - POLYURETHANE HOSES

MAGNUM PU RAME - 0,4mm - IPL



Прозрачен TPU маркуч на естерна основа, подсилен с помеднена стоманена спирала. Постоянна дебелина на стената 0,4mm при всички диаметри. Отлична якост, гъвкавост и свиваемост (прибл. 5:1) за лесно транспортиране и складиране. Добра устойчивост на износване, огъване, минерални масла, стареене, атмосферни влияния, UV лъчи и озон. Може да се заземи (R<10^2 Ohm/m) чрез заземяване на спиралата.
Работна температура: -40°C +90°C
Приложения: дърводелската и дърводобивна промишленост, обезпрашаване, малки промишлени прахосмукачки. За леко изсмукване на абразивен прах и опилки и използване като защитен ръкав.

Transparent, ester-based TPU hose, reinforced with copper-plated steel spiral. Constant wall thickness 0,4mm on all diameters. Excellent strength, flexibility and compressibility (approx. 5:1) for easy transport and storage. Good resistance to abrasion, bending, mineral oils, ageing, weathering, UV radiation and ozone.
Can be made conductive (R<10^2 Ohm/m) by grounding the spiral.
Working temperature: -40°C +90°C
Application: carpentry and wood industry, dedusting, small industrial vacuum cleaners. For light extraction of abrasive dust and sawdust and used as a protective sleeve.

Кат. № / Part. №	вътрешен диаметър / ID		дебелина на стената		работно налягане / WP		радиус на огъване / BR	вак. vac. m H2O	тегло/m weight/m
	mm		mm	inch	bar	psi	mm	bar	kg/m
PUR025L	25		0,4				25	0,40	0,130
PUR030L	30		0,4				25	0,40	0,155
PUR032L	32		0,4				25	0,40	0,160
PUR035L	35		0,4				30	0,40	0,175
PUR040L	40		0,4				30	0,40	0,195
PUR045L	45		0,4				36	0,40	0,220
PUR050L	50		0,4				40	0,40	0,205
PUR060L	60		0,4				50	0,40	0,240
PUR063L	63		0,4				55	0,40	0,250
PUR070L	70		0,4				56	0,40	0,360
PUR075L	75		0,4				60	0,40	0,390
PUR080L	80		0,4				65	0,40	0,410
PUR090L	90		0,4				75	0,40	0,460
PUR100L	100		0,4				85	0,30	0,505
PUR110L	110		0,4				90	0,30	0,555
PUR0114L	114		0,4				95	0,30	0,580
PUR0120L	120		0,4				100	0,25	0,600
PUR125L	125		0,4				105	0,25	0,635
PUR1305L	130		0,4				105	0,20	0,650
PUR140L	140		0,4				115	0,20	0,700
PUR150L	152		0,4				125	0,20	0,755
PUR160L	160		0,4				130	0,15	0,870
PUR170L	170		0,4				130	0,15	0,925
PUR180L	180		0,4				150	0,15	0,975
PUR200L	203		0,4				165	0,10	1,105
PUR225L	225		0,4				185	0,10	1,235
PUR254L	254		0,4				210	0,10	1,375
PUR0275L	275		0,4				230	0,08	1,505
PUR300L	305		0,4				250	0,08	1,645
PUR0350L	350		0,4				300	0,07	1,915