ПОЛИУРЕТАНОВИ МАРКУЧИ - POLYURETHANE HOSES

MAGNUM PU RAME - 0,7mm - IPL



Прозрачен TPU марку на естерна основа, подсилен с помеднена и покрита с TPU стоманена спирала. Напълно гладка вътрешна повърхност, постоянна дебелина на станата от 0,7mm за всички диаметри. Абразивоустойчивост 20 mm3, устойчивост на минерални масла, стареене, озон и много химикали. Антистатичен R<10^9 Ohm/m устойчив на UV. Перфектна устойчивост на хидролитично въздействие. Може да се заземи (R<10^2 Ohm/m) чрез спиралата.
Работна температура: -40°C +90°C
Приложения: Всмукателни инсталации, керамична и дървообраротваща промишленост, засмукване на стърготини, опилки, изпарения, абразивен прах.

Translucent, ester-based TPU hose, reinforced with copper-colored TPU-coated steel spiral. Completely smooth inner surface, constant 0,7mm wall thickness for all diameters. Abrasion resistance 20 mm3, resistant to mineral oils, ageing, ozone and many chemicals. Antistatic R<10^9 Ohm/m, UV resistant. Superior resistance to hydrolytic attack. The hose can be made conductive (R<10^2 Ohm/m) by grounding the spiral.
Working temperature: -40°C +90°C
Application: suction plants, ceramic and wood industry, suction of chips, sawdust, fumes and abrasive dust.

Кат. № / Part. №	вътрешен диаметър / ID		дебелина на стената		работно налягане / WP		радиус на огъване / BR	вак. vac. m H2O	тегло/m weight/m
	mm		mm	inch	bar	psi	mm	bar	kg/m
PUR050	50		0,7				50	2,0	0,365
PUR060	60		0,7				70	1,7	0,480
PUR063	63		0,7				70	1,7	0,515
PUR070	70		0,7				85	1,7	0,565
PUR075	75		0,7				90	1,7	0,585
PUR080	80		0,7				95	1,6	0,615
PUR090	90		0,7				105	1,6	0,690
PUR100	100		0,7				135	1,3	0,830
PUR110	110		0,7				145	1,2	0,875
PUR120	120		0,7				160	1,0	0,960
PUR125	125		0,7				210	1,0	1,000
PUR130	130		0,7				220	1,0	1,015
PUR140	140		0,7				185	0,8	1,045
PUR150	150		0,7				230	0,8	1,225
PUR160	160		0,7				250	0,7	1,325
PUR170	170		0,7				260	0,7	1,390
PUR180	180		0,7				270	0,5	1,490
PUR200	200		0,7				300	0,4	1,850
PUR220	220		0,7						
PUR250	250		0,7						
PUR300	300		0,7						