PTFE Маркучи - PTFE Hoses

гладък PTFE 2 оплетки / smooth PTFE 2 braids




PTFE маркуч, гладък, с две метални оплетки от неръждаема стомана AISI304.
Вътрешна камера: гладка тефлонова вложка, огнеупорна, химически инертна, според FDA нормите.
Външна обвивка: две метални оплетки от неръждаема стомана AISI304.
Температурен режим: -70°C +260°C.
Приложение: за пренос на хранителни продукти, отговаря на FDA нормите. Пренос на химикали във фармацевтичната и козметичната индустрия. Устойчив на силно активни химикали.

PTFE hose, smooth, braided with two stainless steel AISI304 braids.
Tube: smooth PTFE tube, resistant to fire, chemically inert. Suitable for food use acc. to FDA norm.
Cover: two stainless steel AISI304 braids.
Working temperature: -70°C +260°C.
Application: transfer of food products, corresponds to FDA norm. Transfer of chemicals in the pharmaceutical and cosmetic industries. Resistant to hard and active chemicals.

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		радиус на огъване / BR	вак. % vac. %	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	mm	bar	kg/m
PF206	6	1/4"	10,5	13/32"	365	5292	1100	15950	45		0,174
PF210	10	3/8"	14,3	9/16"	285	4132	850	12325	55		0,268
PF212	12	1/2"	17,6	11/16"	280	4060	750	10875	70		0,372
PF216	16	5/8"	21,0	53/64"	235	3407	700	10150	130		0,507
PF220	20	3/4"	24,1	61/64"	200	2900	600	8700	190		0,609
PF225	25	1"	31,5	1,15/64"	150	2175	450	6525	270		0,813

Температура / Temperature: 20º C



Изменение на работното налягане спрямо работната температурата:
Subordination of the working pressure by the working temperature:

TEMPERATURE	PRESSURE
-60°C	95%
20°C	100%
100°C	75%
150°C	50%
200°C	25%
250°C	10%