ХИМИКАЛИ - CHEMICALS

UHMWPE 509OE S&D 16 bar Alfagomma

2004/1935 EC
2006/2023 EC



Смукателно-нагнетателен маркуч за химикали.
Вътрешна камера: Прозрачна, от UHMWPE (Ултра високо молекулен полиетилен).
Вградени текстилни оплетки с висока якост и вградена стоманена спирала.
Външна обвивка: синя EPDM, устойчива на абразии и озон.
Температурен режим: -30°C +100°C в зависимост от пренасяния химикал.
Приложение: за пренос на киселини и химикали. Подходящ за 98% от съществуващите химикали.

Suction and delivery hose for chemicals.
Tube: Transparent UHMWPE (Ultra High Molecular Weight Polyethylene).
Reinforcement: : high tensile textile cords with embedded steel helix wire.
Cover: blue EPDM - abrasion and ozone.
Working temperature: -30°C +100°C depending on conveyed chemical.
Application: acid and chemical suction and delivery. Suitable for 98% of existing chemicals.

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		радиус на огъване / BR	вак. % vac. %	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	mm	bar	kg/m
509020BL	19	3/4"	31	1.22	16	240	48	720	114	90.0	0.590
509025BL	25	1"	37	1.46	16	240	48	720	150	90.0	0.730
509032BL	32	1,1/4"	44	1.73	16	240	48	720	192	90.0	0.880
509038BL	38	1,1/2"	50	1.97	16	240	48	720	228	90.0	1.010
509050BL	51	2"	63	2.48	16	240	48	720	300	90.0	1.340
509063BL	63	2,1/2"	77	3.03	16	240	48	720	378	90.0	2.090
509076BL	76	3"	92	3.62	16	240	48	720	450	80.0	2.840
509100BL	102	4"	118	4.65	16	240	48	720	600	80.0	3.870