ВЪЗДУХ - AIR

PVC Magnum Metal



Смукателно-нагн. прозрачен PVC маркуч, гладък. Може да бъде заземен (R<10^2 Ohm/m) чрез заземяване на спиралата.
Подходящ за храниелни продукти съгласно Reg. EU 10/2011, Classes A, B, and C.

Вътрешна камера: прозрачно PVC. Устойчиво на някои химикали и на атмосферни условия.

Подсилен с метална спирала.

Външна обвивка: прозрачно PVC, устойчиво на някои химикали и на атмосферни условия.

Температурен режим: -10°C +60°C.
Приложение: идеален за пренос на течни храни, напитки, плодови сокове, вино и алкохолни напитки, с алкохолно съдържание до 20%.

Suction and delivery transparent PVC hose, smooth. It can be conductive (R<10^2 Ohm/m) by grounding the spyral.
Suitable for food products according to Reg. EU 10/2011, Classes A, B, and C.

Tube: transparent PVC. Resistant to several chemicals and to weather conditions.

Reinforcement: Steel spyral

Cover: transparent PVC. resistant to several chemicals and to weather conditions.

Working temperature: -10°C + 60°C.
Application: Ideal solution for suction and delivery of food liquids, beverages, fruit juices, wine and liquors with up to 20% alcohol cnoncentration.

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		Вакуум Vacuum	радиус на огъване / BR	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	m H2O	mm	kg/m
MM010	10		16		5,0		25		9,5	50	0,175
MM012	13		19		5,0		25		9,5	60	0,215
MM014	14		20		5,0		25		9,5	60	0,225
MM016	16		22		5,0		25		9,5	70	0,270
MM018	18		26		5,0		25		9,5	80	0,295
MM019	19		22		5,0		25		9,5	90	0,340
MM020	20		28		5,0		25		9,5	90	0,355
MM022	22		30		5,0		25		9,5	100	0,385
MM025	25		33		4,0		20		9,5	110	0,505
MM030	30		38		4,0		20		8,5	140	0,590
MM032	32		40		4,0		20		8,5	140	0,650
MM035	35		45		4,0		20		8,5	160	0,705
MM038	38		48		4,0		20		8,5	170	0,810
MM040	40		50		4,0		20		8,5	180	0,490
MM045	45		55		4,0		20		8	200	1,110
MM050	51		61		4,0		20		8	230	1,265
MM060	60		72		3,6		18		8	270	1,715
MM063	63		75		3,6		18		8	280	1,815
MM070	70		84		3,6		18		7	320	2,035
MM075	76		90		3,6		18		7	340	2,225
MM080	80		94		3,6		18		7	360	2,360
MM090	90		104		3,0		15		7	410	3,030
MM100	102		116		2,4		12		7	460	3,400
MM105	105		121		2,4		12		7	470	3,495
MM125	127		145		1,2		6		9	640	5,570
MM150	152		172		1,2		6		9	760	6,950