ГАЗ ПРОПАН-БУТАН - LPG

PETROGAS SD 25 bar EN1762

*



**



Смукателно-нагнетателен маркуч за LPG, отговарящ на изискванията на EN1762
Вътрешна камера: черна, гладка, електропроводима NBR.
Синтетични оплетки с висока якост и метални спирали.
Външна обвивка: черна, гладка, микроперфорирана негорима и електропрводима CR, устойчива на масла и озон
Температурен режим: -30°C +70°C.
Приложение: Смукателно-нагнетателен маркуч за LPG, съответства на изискванията на EN1762. Подходящ за газ-станции, резервоари,цистерни и др. Също така е подходящ за горива и масла.

Suction and delivery hose for LPG, in accordance with EN1762.
Tube: black, smooth, conductive NBR rubber compound.
Reinforcement: high strength synthetic plies with steel spirals.
Cover: black, smooth, pin pricked, fire proof and conductive CR rubber compound, oils and ozone resistant.
Working temperature: -30°C +70°C.
Application: Suction and delivery hose for LPG, in accordance with EN1762. Suitable for gas stations, cisterns,tanks, truck tanks, etc. Also suitable for fuel and oil.

*** TGT**

**** ALFAGOMMA - подходящ за пренос на LPG от док до кораб и от кораб до кораб поради устойчивост на солена вода и въглеводороди.**

Кат. № / Part. №	вътрешен диаметър / ID		външен диаметър / OD		работно налягане / WP		разрушаващо налягане / BP		радиус на огъване / BR	вак. % vac. %	тегло/m weight/m
	mm	inch	mm	inch	bar	psi	bar	psi	mm	bar	kg/m
LPG025SD*	25	1"	38	1,1/2"	25	375	100	1500	140	90.0	0.900
LPG032SD*	32	1,1/4"	45	1,3/4"	25	375	100	1500	190	90.0	1.180
LPG038SD*	38	1,1/2"	52	2,1/16"	25	375	100	1500	200	90.0	1.500
LPG050SD**	51	2"	69	2,23/32"	25	375	100	1500	306	90.0	2.820
LPG075SD**	76	3"	98	3,55/64	25	375	100	1500	456	90.0	4.680
LPG100SD**	102	4"	126	4,61/64	25	375	100	1500	612	90.0	6.950
LPG150SD**	150	6"	180	7,3/32	25	375	100	1500	912	90.0	12.360

1.