СИЛИКОНОВ АСПИРАЦИОНЕН МАРКУЧ - ASPIRATIONAL SILICONE HOSE

MAGNUM SIL II



Червено-кафяв маркуч от фибро стъкло със силиконова обвивка, двупластов.
Маркучът е подсилен със стоманена спирала.
Подходящ за висока температура, гъвкав при ниски температури, много добра издържливост на химиккали.
Работна температура: -70°C +250 (кратки пикове до +300°C)
Приложение: подгохящ за горещ въздух, газове при вентилационни и апирационни системи, хартиената промишленост, производството на пластмаси, автомобилостроенето и др.

Red-brown silicone-coated-glassfabric, double-ply.
The hose is reinforced with a steel spiral.
It has excellent heat resistance, maintains flexibility at low temperatures, very good chemical resistance.
Working temperature: -70°C +250°C (interm. Up to +300°C).
Application: suction of hot air and gases in ventilation and aspiraton systems, industrial use in paper processing factories, plastic industry, vehicle construction and others.

Кат. № / Part. №	вътрешен диаметър / ID		дебелина на стената		работно налягане / WP		радиус на огъване / BR	Вакуум макс. Max.Vacuum	тегло/m weight/m
	mm		mm	inch	bar	psi	mm	bar	kg/m
FP4S2050	51		0.4		2.6		51	0.52	0.200
FP4S2055	55		0.4		2.3		55	0.53	0.250
FP4S2060	60		0.4		2.2		60	0.53	0.310
FP4S2063	63		0.4		2.4		63	0.48	0.440
FP4S2070	70		0.4		2.3		70	0.44	0.460
FP4S2075	76		0.4		2.2		76	0.43	0.500
FP4S2080	80		0.4		2.1		80	0.40	0.580
FP4S2090	90		0.4		2		90	0.40	0.610
FP4S2100	102		0.4		1.9		102	0.35	0.660
FP4S2110	110		0.4		1.7		110	0.30	0.720
FP4S2114	114		0.4				114	0.26	0.830
FP4S2120	120		0.4		1.5		120	0.21	0.940
FP4S2130	130		0.4		1.4		130	0.25	1.010
FP4S2140	140		0.4		1.3		140	0.19	1.090
FP4S2150	152		0.4		1.2		152	0.12	1.330
FP4S2160	160		0.4		0.9		160	0.15	1.480