МАРКУЧ ЗА ХРАНИ И АГРО МАШИНИ PVC- FOOD AND AGRO-HOSE PVC

TROY LD - FITT Aliflex

FCM - European Regulation 10/2011 for Simulants A-B-C-D1



Устойчив на механично увреждане смукателно-нагнетателен маркуч, сертифициран за течни храни.
Структура: PVC спирален маркуч, подсилен с твърда, удароустойчива PVC спирала.
Маркучът има висока механична якост, висока издъжливост, добра гъвкавост.
Работна температура: -10°C +60°C.
Приложение: Маркуч за тежък режим на работа, подходящ за ХВП сектора, както и за агро машини.

Resistant to crushing, this hose is certified for the sucton and delivery of liquid foods.
Structure: PVC spiral hose, reinforced with a PVC rigid shock-resistant spiral.
The hose has high crushing resistance, high and long durability and good flexibility.
Working temperature: -10°C +60°C.
Application: Heavy duty hose for installation on food sector and agricultural machinery.

Кат. № / Part. №	вътрешен диаметър / ID		дебелина на стената		работно налягане / WP		радиус на огъване / BR	Вакуум Vacuum	тегло/m weight/m
	mm		mm	inch	bar	psi	mm	m H2O	kg/m
TROY020LD	20		2.8		7	101	100	6.0	0.210
TROY025LD	25		3.0		7	101	120	6.0	0.280
TROY030LD	30		3.2		7	101	140	6.0	0.350
TROY032LD	32		3.2		7	101	160	6.0	0.370
TROY035LD	35		3.3		7	101	170	6.0	0.425
TROY038LD	38		3.4		6	87	190	6.0	0.470
TROY040LD	40		3.5		6	87	200	6.0	0.510
TROY045LD	45		3.6		6	87	230	6.0	0.570
TROY050LD	51		3.9		6	87	250	6.0	0.730
TROY060LD	60		4.2		6	87	320	6.0	0.900
TROY063LD	63		4.2		5	72	330	6.0	0.970
TROY076LD	76		4.7		5	72	400	6.0	1.270
TROY100LD	100		5.4		4	58	550	5.0	1.950