ПОЛИУРЕТАНОВ МАРКУЧ ЗА СЕЯЛКИ - POLYURETHANE HOSE FOR SSEDINGS

# MAGNUM AIR PU - 0,4mm - 0,5mm IPL



**Прозрачен TPU маркуч на естерна основа, подсилен със сива противоударна твърда PVC спирала.**
**Дебелина на стената от 0,4 до 0,8mm. Абсолютно гладка вътрешна повърхност за оптимизиране на потока**
**Устойчив на абразия и усукване. Добра устойчивост на повечето химикали, UV лъчи, озон.**
**По заявка може да се произведе в антистатичен вариант, с меден проводник за заземяване и да бъде предпазен от антистатично електричество, или в постоянното антистатично изпълнение (код OU86).**
**Работна температура: -40°C +80°C**
**Приложения: засмукване на абразивни продукти като прахови частици, пелети, гранулати. Може да се използва за обезпрашавае и индустриално почистване.**

**Transparent, ester-based TPU hose, reinforced with a dark grey anti-shock rigid PVC spiral.**
**Wall thickness from 0,4mm to 0,8mm. Inner surface completely smooth to maximise optimal flow.**
**Resistant to abrasion and torsion. It has good resistance to most chemicals, UV, ozone and atmospherical agents.**
**On request it can be manufactured in the antistatic version, with copper wire for earthing to protect against static dissipation or in the permanent antistatic version (cod. OU86)**
**Working temperature: -40°C +80°C**
**Application: suction of abrasive media such as powders, pellets, granulates, fibres, can be used for dedusting and industrial cleaning.**

| Кат. № / Part. № | вътрешен диаметър / ID | | дебелина на стената | | работно налягане / WP | | радиус на огъване / BR | вак. vac. m H2O | тегло/m weight/m |
|---|---|---|---|---|---|---|---|---|---|
| | mm | | mm | inch | bar | psi | mm | bar | kg/m |
| **PU025** | 25 | | 0.4 | | | | 30 | 2.50 | 0.140 |
| **PU030** | 30 | | 0.4 | | | | 35 | 2.00 | 0.170 |
| **PU032** | 32 | | 0.4 | | | | 35 | 2.00 | 0.190 |
| **PU035** | 35 | | 0.5 | | | | 45 | 2.00 | 0.200 |
| **PU038** | 38 | | 0.5 | | | | 50 | 2.00 | 0.230 |
| **PU040** | 40 | | 0.5 | | | | 60 | 2.00 | 0.240 |
| **PU045** | 45 | | 0.5 | | | | 65 | 2.00 | 0.290 |
| **PU050** | 50 | | 0.5 | | | | 70 | 2.00 | 0.330 |