EPDM/PP МАРКУЧ - EPDM/PP HOSE

MAGNUM 178 AA - Alfagomma



Черен EPDM/PP, изцяло рециклируем, не съдържа халогени/фталати. Много лек и лесен за работа.
Маркучът е подсилен със спирала.
Има изключителна гъвкавост, като стойността на радиусът му на огъване е по-ниска от диаметъра.
Работна температура: -40°C +120°C
Приложение: подгохящ за горещ въздух, газове, вентилационни и апирационни системи, горещи отпадъци.
Приложения, при които се изисква издържливост на висока температура на маркуча.

Black EPDM/PP fully recyclable and halogens/phthaltates free. Very light and easy to handle with.
The hose is reinforced with steel helix wire.
It has outstanding flexability, as the bending radius value is lower than the diameter of the hose.
Working temperature: -40°C +120°C
Application: suitable for hot air, gas, fumes extraction ventilations, dust, hot waste, where high temperature resistance is required.

Кат. № / Part. №	вътрешен диаметър / ID		дебелина на стената		работно налягане / WP		радиус на огъване / BR	вак. vac. m H2O	тегло/m weight/m
	mm		mm	inch	bar	psi	mm	bar	kg/m
178AA040	40	1.9/16"					32		0.200
178AA050	51	2"					40		0.250
178AA063	63	2.1/2"					55		0.310
178AA070	70	2.3/4"					60		0.440
178AA075	76	3"					65		0.460
178AA080	80	3.1/8"					65		0.500
178AA090	90	3.1/2"					75		0.580
178AA100	102	4"					85		0.610
178AA110	110	4.5/16"					0		0.660
178AA120	120	4.3/4"					100		0.720
178AA127	127	5"					105		0.830
178AA140	140	5.1/2"					115		0.940
178AA150	152	6"					125		1.010
178AA160	160	6.5/16"					130		1.090
178AA180	180	7.1/16"					150		1.330
178AA200	203	8"					165		1.480
178AA250	254	10"					210		1.930
178AA300	305	12"					250		2.380
178AA355	355	14"					300		2.770
178AA400	406	16"					350		3.210